

9 x 21 mm



90 gr. Jacketed HP 1.063" OAL

BC: .115
SD: .102

Powder	Sugg Starting Grains	Velocity fps	Pressure C.U.P.	Max Load Grains	Velocity fps	Pressure C.U.P.
700X	4.5	1127	21,000	5.9	1419	31,800
SR-4756	6.9	1293	22,500	8.0+	1480	31,000
Bullseye ✓	5.5	1290	26,000	7.2	1446	31,700
Unique ✓	5.2	1219	23,200	6.6	1402	32,000
Blue Dot ✓	8.7	1349	24,900	10.2+	1482	28,600
HS-6	7.7	1274	23,800	9.0	1411	31,700
AA#5 A	6.5	1195	20,300	7.8	1463	31,500
231	5.2	1234	24,000	6.5	1456	30,800



115 gr. Jacketed HP 1.063" OAL

BC: .155
SD: .130

Powder	Sugg Starting Grains	Velocity fps	Pressure C.U.P.	Max Load Grains	Velocity fps	Pressure C.U.P.
700X	4.0	882	22,000	5.5	1295	31,500
SR-4756	5.8	1119	24,600	7.0+	1323	32,800
Bullseye ✓	4.5	935	23,000	5.8	1234	29,600
Unique ✓	5.0	995	24,800	6.2	1317	31,000
Blue Dot →	8.0	1180	25,100	9.3+	1333	29,400
HS-6	6.8	1048	24,400	8.1	1305	31,300
AA#7 H	8.0	979	20,500	10.0	1330	30,000
231	5.0	1028	25,200	6.3	1266	31,500



124 gr. FMJ/FP 1.090" OAL

BC: .174
SD: .141

Powder	Sugg Starting Grains	Velocity fps	Pressure C.U.P.	Max Load Grains	Velocity fps	Pressure C.U.P.
700X	4.0	868	22,000	5.4	1235	31,500
SR-4756	5.0	887	20,800	6.5	1222	31,000
Bullseye ✓	4.2	853	20,000	5.7	1242	29,400
Unique ✓	4.5	909	20,500	5.8	1259	31,100
Blue Dot ✓	7.3	1066	24,100	8.7+	1291	30,400
HS-6	6.5	937	21,500	7.8	1289	31,700
AA#7 ↗	7.3	928	19,800	9.8	1335	32,100
231	4.5	930	20,000	6.1	1235	30,100



130 gr. FMJ 1.169" OAL

BC: .160
SD: .147

Powder	Sugg Starting Grains	Velocity fps	Pressure C.U.P.	Max Load Grains	Velocity fps	Pressure C.U.P.
700X	3.7	761	18,500	5.1	1069	31,400
WSF	5.5	918	25,500	6.4	1128	31,500
Bullseye ✓	4.0	811	19,800	5.6	1021	29,100
Unique ✓	5.2	947	20,600	6.3	1179	29,200
Blue Dot ✓	7.2	964	23,800	8.5	1247	31,100
HS-6	6.5	898	21,900	7.7	1173	29,400
AA#7 ↗	8.1	964	23,000	9.7	1284	31,800
231	4.6	873	23,500	5.6	1141	31,400

Note: Loads shown in shaded panels are maximum.
Loads shown in bold designate potentially most accurate load.
+Designates a compressed powder charge.

9 x 21 mm



147 gr. TMJ
1.169" OAL

BC: .208
SD: .167

Powder	Sugg Starting Grains	Velocity fps	Pressure C.U.P.	Max Load Grains	Velocity fps	Pressure C.U.P.
WSF	5.1	856	24,700	6.2	1144	33,000
231	4.2	762	20,000	5.4	1047	31,400
Blue Dot	5.7	642	20,000	7.8	1100	31,400
HS-6	5.9	785	24,400	7.4	1159	33,000
AA#7	7.4	856	24,600	9.2	1228	33,000



#356402
120 gr. (#2 Alloy) 1.169" OAL

BC: .146
SD: .136

Powder	Sugg Starting Grains	Velocity fps	Pressure C.U.P.	Max Load Grains	Velocity fps	Pressure C.U.P.
700X	3.6	868	23,900	5.2	1292	34,000
SR-4756	4.8	826	18,100	6.0	1228	29,500
Bullseye	3.8	836	18,200	5.4	1242	29,700
Unique	4.3	888	21,000	5.6	1269	31,000
Blue Dot	7.0	1031	23,200	8.4+	1279	29,500
HS-6	6.1	934	20,500	7.4	1287	31,800
AA#5	5.4	951	20,800	6.5	1268	31,800
231	4.1	870	20,000	5.7	1252	30,300



#356637
147 gr. (#2 Alloy) 1.119" OAL

BC: .073
SD: .167

Powder	Sugg Starting Grains	Velocity fps	Pressure C.U.P.	Max Load Grains	Velocity fps	Pressure C.U.P.
SR-4756	4.0	767	23,300	4.7	930	31,800
Bullseye	3.4	700	22,600	4.5	1005	32,200
Unique	3.3	667	22,300	4.4	925	30,100
Blue Dot	5.1	775	18,900	7.0	1037	29,300
HS-6	4.6	683	22,200	6.0	1040	31,500
AA#7	6.0	705	18,800	8.0	1089	29,600
231	3.0	756	22,000	5.0	1065	31,300

Note: Loads shown in shaded panels are maximum.
Loads shown in bold designate potentially most accurate load.
+Designates a compressed powder charge.